



CODE QUIZ - September 2026

1. Per the 2025 California Building Code Section 415.6, Group H occupancies shall be located on property in accordance with the other provisions of this chapter. In Groups H-2 & H-3 occupancies, not less than _____ percent of the perimeter wall shall be an exterior wall.
 - a. 10
 - b. 25
 - c. 50
 - d. 100
2. Per California Building Code Section 3109, Swimming Pools, Spas, and Hot Tubs, the latch for a swimming pool safety barrier shall be no lower than _____?
 - a. 54 inches above the walking surface.
 - b. 60 inches above the walking surface.
 - c. 64 inches above the walking surface.
 - d. California Building Code Section 3109 was not adopted by HCD thus is not enforceable.
3. Per the California Swimming Pool Safety Act 115922 and 115923, CBC Section 3109.2, for swimming pools at a private single-family home the enclosure that isolates the swimming pool or spa from the private single-family home shall have a minimum height of ____ inches with a self-latching gate with the self-latching device placed no lower than ____ inches above ground.
 - a. 48 inches, and 48 inches.
 - b. 54 inches, and 54 inches.
 - c. 60 inches, and 54 inches.
 - d. 60 inches, and 60 inches.
4. Per the California Swimming Pool Safety Act 115922 and 115923, CBC Section 3109.2, for a pool or spa at a private single-family home, exit alarms may be used as one of the two required drowning prevention safety features on the private single-family homes _____ that provide direct access to the swimming pool or spa without any intervening enclosure.
 - a. Doors.
 - b. Doors and windows.
 - c. Doggy doors.
 - d. a. and b.
 - e. All of the above.
5. The requirements of the Swimming Pool Safety Act 115925, CBC Section 3109.2, do not apply to the following _____.
 - a. Homes on 1 acre or more.
 - b. Pools in an apartment complex.
 - c. Public swimming pools.
 - d. All of the above
 - e. b. and c.

Answer Key: 1: b 2: d 3: d 4: e 5: e

Please contact Ron Beehler by email at rbeehler@bpr-grp.com to discuss any questions.